



19 PIN Cable

PART NUMBER	DESCRIPTION	WEIGHT
1400-02-33-01-001	100FT	56lbs.
1400-02-33-02-001	75FT	40lbs.
1400-02-33-03-001	50FT	28lbs.
1400-02-33-04-001	25FT	14lbs.
1400-02-33-06-001	5FT	3lbs.
1400-02-33-07-001	10FT	6lbs.
1400-02-33-08-001	125FT	70lbs.
1400-02-33-09-001	150FT	84lbs.
1400-02-33-10-001	200FT	112lbs.
1400-02-33-99-001	Custom Length	TBD

CABLE SPECIFICATIONS

CONNECTOR	19 Pin, Circular Series, VSC Compatible, Aluminum Body, Crimp or Solder, UL/CSA
STRAIN RELIEF	Dome-Nut, Nylon, PG Thread
CABLE	12/14 TYPE AWM 600V 90°C Non-UL Listed
GROUND RING	No Ground Ring, Pins 13 - 18 Are Not Bonded

Cables have a 6" length of clear heatshrink installed on each end to allow the end user to activate over any labels or information applied to the cable.

1.800.227.6784 FOR MORE INFORMATION
<http://www.motionlabs.com/>

520 Furnace Dock Road . Cortlandt Manor, New York 10567 . Phone: (914)788-8877 Fax: (914)788-8866